

VMD-08

KEY FEATURES:

- 8 l/min of dry air
- Compact size
- Wall mountable
- Easy to use
- Powder coated Al. Cabinet

PRODUCT DESCRIPTION

The VMD-08 is a wall mountable Air dryer unit. It can supply up to 8 l/min of dry air under normal conditions. The VMD-08 is used to supply a dry air source for units that use less than 8 l/min such as the HTU-500 and VMUS-4.



AZCO INDUSTRIES LIMITED
ADVANCED OZONE SYSTEMS

SPECIFICATIONS

	VMD-08	VMD-30	AS-12
General			
Voltage [VAC, 50/60Hz]	100-240	100-120	100-120 (200-240)
Power Consumption [W]	Max. 125	Max. 250	Max. 480W
Ambient Temperature [°C]	2 to 28		
Relative Humidity [%]	92		
Mass [Kg]	3.0	7.2	28 (29.5)
Dimensions [H x W x D] [mm] <i>1 mm = .039 inches</i>	370 x 222 x 80	453 x 260 x 100	680 x 440 x 250
Installation	Refer to AZCO's installation manual for specific product		
Warranty [Refer to AZCO warranty sheet]	3 Year		
Ozone			
Generation Process	N/A	N/A	N/A
Process Gas [bar] <i>1 bar = 14.5 psi</i>	Ambient air, free of dust and oil. Maximum pressure \pm 0.36		Upto 0.35
Production	8 l/min @ 25°C and 75% R.H.	30 l/min @ 25°C and 75% R.H.	6 l/min of 98% oxygen
Options			
Internal Air Pump	N/A	N/A	N/A
Adjustable Output	N/A	N/A	N/A
Interlock	N/A	N/A	N/A
Flow Meter	N/A	N/A	N/A
Oxygen Ready	N/A	N/A	N/A
Vacuum Switch	N/A	N/A	N/A
Built-in Air Dryer	N/A	N/A	N/A
Safety			



E*: European Version, N/A: Not Applicable, O: Optional, S: Standard